



### **Face Material**

High gloss wood free paper

Type	Coated paper	
Colour and Finish	White	
Weight	80 gsm $\pm$ 3%	ISO 536
Thickness	65 $\mu$ $\pm$ 4%	ISO 534

### **Application**

Specially designed for general and promotional labels in consumer product

### **Printing Methods**

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

### **Adhesive**

Special purpose permanent, rubber based adhesive

Type	Rubber permanent	
Min. Appl.Temp	0°c	
Service TEMP	-40/+50 °c	
Initial Tack	9 N/25mm	FINAT FTM 9
Shear	Very High	FINAT FTM18
Final Adhesion	6 N/25mm	FINAT FTM 2

### **Shelf life**

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 °c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

### **Liner**

Type	One side siliconized Glassine	
Colour and Finish	White	
Weight	62 gsm $\pm$ 5%	ISO 536
Thickness	52 $\mu$ $\pm$ 5%	ISO 534
Transparency	>50%	DIN 53 147-46