



Face Material

Gloss wood free paper

Type	Coated paper	
Colour and Finish	White	
Weight	80 gsm $\pm$ 3%	ISO 536
Thickness	65 μ $\pm$ 4%	ISO 534

Application

Specially designed suitable for deep freeze applications onto cold surfaces with very good adhesion labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Adhesive

A general purpose permanent, rubber based adhesive

Type	Rubber permanent	
Min. Appl.Temp	0 $^{\circ}$ c	
Service TEMP	-30/+70 $^{\circ}$ c	
Initial Tack	14 N/25mm	FINAT FTM 9
Shear	Very High	FINAT FTM18
Final Adhesion	10 N/25mm	FINAT FTM 2

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 $^{\circ}$ c and 50 $\pm$ 5 $^{\circ}$ c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

Liner

Type	One side siliconized Glassine	
Colour and Finish	White	
Weight	60 gsm $\pm$ 5%	ISO 536
Thickness	55 μ $\pm$ 5%	ISO 534
Transparency	>50%	DIN 53 147-46