



### **Face Material**

High gloss wood free paper

|                   |                   |         |
|-------------------|-------------------|---------|
| Type              | Coated paper      |         |
| Colour and Finish | White             |         |
| Weight            | 80 gsm $\pm$ 3%   | ISO 536 |
| Thickness         | 65 $\mu$ $\pm$ 4% | ISO 534 |

### **Adhesive**

A general purpose permanent, rubber based adhesive

|                |                  |             |
|----------------|------------------|-------------|
| Type           | Rubber permanent |             |
| Min. Appl.Temp | 0°C              |             |
| Service TEMP   | -30/+70 °c       |             |
| Initial Tack   | 14 N/25mm        | FINAT FTM 9 |
| Shear          | Very High        | FINAT FTM18 |
| Final Adhesion | 10 N/25mm        | FINAT FTM 2 |

### **Liner**

|                   |                               |               |
|-------------------|-------------------------------|---------------|
| Type              | One side siliconized Glassine |               |
| Colour and Finish | Yellow                        |               |
| Weight            | 62 gsm $\pm$ 5%               | ISO 536       |
| Thickness         | 52 $\mu$ $\pm$ 5%             | ISO 534       |
| Transparency      | >50%                          | DIN 53 147-46 |

### **Application**

Specially designed for general and promotional labels in consumer product

### **Printing Methods**

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

### **Shelf life**

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 °c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.