



### **Face Material**

High gloss wood free paper

Type Coated paper

Colour and Finish White

Weight 80 gsm  $\pm$  3% ISO 536

Thickness 65  $\mu$   $\pm$  4% ISO 534

### **Adhesive**

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type Acrylic based

Min. Appl.Temp 0°C

Service TEMP -20/+80 °c

Initial Tack 8 N/25mm FINAT FTM 9

Shear High FINAT FTM18

Final Adhesion 9 N/25mm FINAT FTM 2

### **Application**

Specially designed for general and promotional labels in consumer product

### **Printing Methods**

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

### **Shelf life**

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 °c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

### **Liner**

Type One side siliconised Glassine

Colour and Finish Yellow

Weight 60 gsm  $\pm$  5% ISO 536

Thickness 55  $\mu$   $\pm$  5% ISO 534

Transparency >50% DIN 53 147-46