



Face Material

High gloss wood free paper

Type	Coated paper	
Colour and Finish	White	
Weight	90 gsm \pm 3%	ISO 536
Thickness	80 μ \pm 4%	ISO 534

Application

Specially designed for logistics and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type	Acrylic based	
Min. Appl.Temp	0 $^{\circ}$ c	
Service TEMP	-20/+80 $^{\circ}$ c	
Initial Tack	8 N/25mm	FINAT FTM 9
Shear	High	FINAT FTM18
Final Adhesion	9 N/25mm	FINAT FTM 2

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 \pm 2 $^{\circ}$ c and 50 \pm 5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	60 gsm \pm 5%	ISO 536
Thickness	55 μ \pm 5%	ISO 534
Transparency	>50%	DIN 53 147-46