



Face Material

High gloss wood free paper

Type Coated paper

Colour and Finish White

Weight 70 gsm $\pm$ 3% ISO 536

Thickness 56 μ $\pm$ 4% ISO 534

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type Acrylic based

Min. Appl.Temp 0°C

Service TEMP -20/+80 °c

Initial Tack 8 N/25mm FINAT FTM 9

Shear High FINAT FTM18

Final Adhesion 9 N/25mm FINAT FTM 2

Application

Labels on curved and cylindrical surfaces even with low diameters, e.g. cosmetic containers.

Printing Methods

Printable with letterpress, flexo, offset and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

Liner

Type One side siliconised Glassine

Colour and Finish Yellow

Weight 62 gsm $\pm$ 5% ISO 536

Thickness 53 μ $\pm$ 5% ISO 534

Transparency >50% DIN 53 147-46