



Face Material

High gloss cast coated paper

Type Coated paper

Colour and Finish White

Weight 80 gsm $\pm$ 3% ISO 536

Thickness 80 μ $\pm$ 4% ISO 534

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type Acrylic based

Min. Appl.Temp 0°C

Service TEMP -20/+80 °C

Initial Tack 10 N/25mm FINAT FTM 9

Shear High FINAT FTM18

Final Adhesion 8 N/25mm FINAT FTM 2

Application

Specially designed for Logistics and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo, offset and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °C and 50 $\pm$ 5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

Liner

Type One side siliconized Glassine

Colour and Finish White

Weight 60 gsm $\pm$ 5% ISO 536

Thickness 55 μ $\pm$ 5% ISO 534

Transparency >50% DIN 53 147-46