

Face Material

High gloss wood free paper

Type Coated paper

Colour and Finish White

Weight 90 gsm $\pm$ 3% ISO 536

Thickness 72 μ $\pm$ 4% ISO 534

Adhesive

A general purpose permanent, rubber based adhesive

Type Rubber permanent

Min. Appl.Temp 0 $^{\circ}$ c

Service TEMP -30/+70 $^{\circ}$ c

Initial Tack 14 N/25mm FINAT FTM 9

Shear Very High FINAT FTM18

Final Adhesion 10 N/25mm FINAT FTM 2

Application

Specially designed for promotional labels in consumer product

Printing Methods

Printable with offset and letterpress.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 $^{\circ}$ c and 50 $\pm$ 5 $^{\circ}$ c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

Liner

Type One side Siliconized PE coated kraft paper

Colour and Finish Yellow

Weight 105 gsm $\pm$ 5% ISO 536

Thickness 105 μ $\pm$ 5% ISO 534

Transparency >50% DIN 53 147-46