



Technical data sheet  
ROLL LABEL- BOPP film  
1102520 PP Pearlized Gloss 66 TC - HTM D.F. - HG 59

Issue date: Jun-2015

### **Face Material**

Gloss white top coated cavitated polypropylene

Type Top coated cavitated polypropylene

Colour and Finish Pearlized

Weight 46 gsm  $\pm$  10% ISO 536

Thickness 66  $\mu$   $\pm$  10% ISO 534

### **Adhesive**

Special purpose permanent, rubber based adhesive

Type Rubber permanent

Min. Appl.Temp 0 $^{\circ}$ C

Service TEMP -40/+50  $^{\circ}$ C

Initial Tack 9 N/25mm FINAT FTM 9

Shear Very High FINAT FTM18

Final Adhesion 7 N/25mm FINAT FTM 2

### **Application**

Specially designed for promotional labels in consumer product

### **Printing Methods**

Printable with letterpress, flexo , offset and gravure.  
Please turn off corona unit before printing.

Testing for suitability between media , printers and inks is always recommended prior to use.

### **Shelf life**

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2  $^{\circ}$ C and 50 $\pm$ 5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

### **Liner**

Type One side siliconized Glassine

Colour and finish Honey

Weight 59 gsm  $\pm$  5% ISO 536

Thickness 52  $\mu$   $\pm$  5% ISO 534

Transparency >50% DIN 53 147-46