

Technical data sheet
ROLL LABEL –BOPP film
11013034 PP Silver 51 TC - HTM .GN - WG 59

Issue date: Jun-2015

Face Material

Gloss silver metallized top coated polypropylene.

Type Top coated polypropylene

Colour and Finish Gloss silver

Weight 47 gsm ± 10% ISO 536

Thickness $51 \mu \pm 10\%$ ISO 534

Adhesive

A general purpose permanent, rubber based adhesive

Type Rubber permanent

Min. Appl.Temp 0°c

Service TEMP -30/+70 °c

Initial Tack 10 N/25mm FINAT FTM 9

Shear Very High FINAT FTM18

Final Adhesion 11 N/25mm FINAT FTM 2

Application

Specially designed for logistics and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo, offset and gravure.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23±2 °c and 50±5 °c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

<u>Liner</u>

Type One side siliconised Glassine

Colour and Finish White

Weight $60 \text{ gsm } \pm 5\%$ ISO 536

Thickness 55 μ ± 5% ISO 534

Transparency >50% DIN 53 147-46