



Technical data sheet  
ROLL LABEL –BOPP film  
11013201 PP Silver 51 TC - HTM GN - HG 59

Issue date: Jun-2015

### **Face Material**

Gloss silver metallized top coated polypropylene.

|                   |                          |         |
|-------------------|--------------------------|---------|
| Type              | Top coated polypropylene |         |
| Colour and Finish | Gloss silver             |         |
| Weight            | 47 gsm $\pm$ 10%         | ISO 536 |
| Thickness         | 51 $\mu$ $\pm$ 10%       | ISO 534 |

### **Adhesive**

A general purpose permanent, rubber based adhesive

|                |                  |             |
|----------------|------------------|-------------|
| Type           | Rubber permanent |             |
| Min. Appl.Temp | 0 °c             |             |
| Service TEMP   | -30/+70 °c       |             |
| Initial Tack   | 10 N/25mm        | FINAT FTM 9 |
| Shear          | Very High        | FINAT FTM18 |
| Final Adhesion | 6 N/25mm         | FINAT FTM 2 |

### **Liner**

|                   |                               |               |
|-------------------|-------------------------------|---------------|
| Type              | One side siliconized glassine |               |
| Colour and Finish | Honey                         |               |
| Weight            | 59 gsm $\pm$ 5%               | ISO 536       |
| Thickness         | 55 $\mu$ $\pm$ 5%             | ISO 534       |
| Transparency      | >50%                          | DIN 53 147-46 |

### **Application**

Specially designed for logistics and promotional labels in consumer product

### **Printing Methods**

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

### **Shelf life**

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.