



Face Material

High gloss cast coated wood free paper

Type	Cast Coated paper	
Colour and Finish	White	
Weight	90 gsm $\pm$ 3%	ISO 536
Thickness	95 μ $\pm$ 4%	ISO 534

Adhesive

A general purpose permanent, rubber based adhesive

Type	Rubber permanent	
Min. Appl.Temp	0°C	
Service TEMP	-30/+70 °c	
Initial Tack	14 N/25mm	FINAT FTM 9
Shear	Very High	FINAT FTM18
Final Adhesion	10 N/25mm	FINAT FTM 2

Liner

Type	One side siliconized PE coated kraft paper	
Colour and Finish	Yellow	
Weight	100 gsm $\pm$ 5%	ISO 536
Thickness	110 μ $\pm$ 5%	ISO 534
Transparency	>50%	DIN 53 147-46

Specially designed for promotional labels in consumer product

Printing Methods

Printable with offset and letterpress.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 °c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.

Application