



### **Face Material**

Gloss silver metallized woodfree paper.

Type	Metallized Paper	
Colour and Finish	Gloss silver	
Weight	73 gsm $\pm$ 3%	ISO 536
Thickness	65 $\mu$ $\pm$ 4%	ISO 534

### **Adhesive**

A general purpose permanent, rubber based adhesive

Type	Rubber permanent	
Min. Appl.Temp	20°c	
Service TEMP	-30/+70 °c	
Initial Tack	10 N/25mm	FINAT FTM 9
Shear	Very High	FINAT FTM18
Final Adhesion	11 N/25mm	FINAT FTM 2

### **Liner**

Type	One side Siliconized Glassine	
Colour and Finish	White	
Weight	60 gsm $\pm$ 5%	ISO 536
Thickness	55 $\mu$ $\pm$ 5%	ISO 534
Transparency	>50%	DIN 53 147-46

### **Application**

Specially designed for promotional labels in consumer product

### **Printing Methods**

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

### **Shelf life**

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 °c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.