



Face Material

Gloss silver metallized woodfree paper.

| | | |
|-------------------|-------------------|---------|
| Type | Metallized Paper | |
| Colour and Finish | Gloss silver | |
| Weight | 73 gsm \pm 3% | ISO 536 |
| Thickness | 65 μ \pm 4% | ISO 534 |

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

| | | |
|----------------|----------------------|-------------|
| Type | Acrylic based | |
| Min. Appl.Temp | 20 $^{\circ}$ c | |
| Service TEMP | -20/+80 $^{\circ}$ c | |
| Initial Tack | 10 N/25mm | FINAT FTM 9 |
| Shear | High | FINAT FTM18 |
| Final Adhesion | 11 N/25mm | FINAT FTM 2 |

Liner

| | | |
|-------------------|-------------------------------|---------------|
| Type | One side Siliconized Glassine | |
| Colour and Finish | White | |
| Weight | 60 gsm \pm 5% | ISO 536 |
| Thickness | 55 μ \pm 5% | ISO 534 |
| Transparency | >50% | DIN 53 147-46 |

Application

Specially designed for promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 \pm 2 $^{\circ}$ c and 50 \pm 5 $^{\circ}$ c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.