



Face Material

Gloss silver metallized woodfree paper.

Type	Metallized Paper	
Colour and Finish	Gloss silver	
Weight	73 gsm \pm 3%	ISO 536
Thickness	65 μ \pm 4%	ISO 534

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type	Acrylic based	
Min. Appl.Temp	0 $^{\circ}$ c	
Service TEMP	-20/+80 $^{\circ}$ c	
Initial Tack	10 N/25mm	FINAT FTM 9
Shear	High	FINAT FTM18
Final Adhesion	9 N/25mm	FINAT FTM 2

Liner

Type	One side Siliconized Glassine	
Colour and Finish	Yellow	
Weight	62 gsm \pm 5%	ISO 536
Thickness	55 μ \pm 5%	ISO 534
Transparency	>50%	DIN 53 147-46

Application

Specially designed for promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 \pm 2 $^{\circ}$ c and 50 \pm 5 $^{\circ}$ c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.