



Face Material

Transparent PET		
Type	Polyester film	
Colour and Finish	Transparent	
Weight	70 gsm ± 3%	ISO 536
Thickness	50 µ ± 4%	ISO 534
Transparency	>96%	DIN 53 147-46

Second Liner

Type	One side siliconised polyester	
Colour and Finish	Transparent	
Weight	70 gsm ±5%	ISO 536
Thickness	50 µ ± 5%	ISO 534
Transparency	>96%	DIN 53 147-46

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type	Acrylic based	
Min. Appl.Temp	0°c	
Service TEMP	-20/+80 °c	
Initial Tack	8 N/25mm	FINAT FTM 9
Shear	High	FINAT FTM18
Final Adhesion	9 N/25mm	FINAT FTM 2

Third Liner

Type	One side siliconized glassine paper	
Colour and Finish	White	
Weight	60 gsm ±5%	ISO 536
Thickness	55 µ ± 5%	ISO 534
Transparency	>50%	DIN 53 147-46

Application

Specially designed for logistics and promotional labels in consumer product

First Liner

Type	One side siliconised polyester	
Colour and Finish	Transparent	
Weight	70 gsm ±5%	ISO 536
Thickness	50 µ ± 5%	ISO 534
Transparency	>96%	DIN 53 147-46

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23±2 °c and 50±5 % of relative Humidity.)
Keep the material in the original packaging when not used in order to protect it from dust and contamination
Do not expose to direct sunlight or heat sources.