



Face Material

| | | |
|--------------------------------------|--------------------|---------|
| Gloss clear top coated polypropylene | | |
| Type | BOPP film | |
| Colour and Finish | Transparent | |
| Weight | 52 gsm \pm 10% | ISO 536 |
| Thickness | 55 μ \pm 10% | ISO 534 |

Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

| | | |
|----------------|---------------|-------------|
| Type | Acrylic based | |
| Min. Appl.Temp | 0°c | |
| Service TEMP | -20/+80 °c | |
| Initial Tack | 9 N/25mm | FINAT FTM 9 |
| Shear | High | FINAT FTM18 |
| Final Adhesion | 7 N/25mm | FINAT FTM 2 |

Liner

| | | |
|-------------------|--------------------------------|---------------|
| Type | One side siliconized polyester | |
| Colour and Finish | Transparent | |
| Weight | 50 gsm \pm 5% | ISO 536 |
| Thickness | 36 μ \pm 5% | ISO 534 |
| Transparency | >96% | DIN 53 147-46 |

Application

Specially designed for logistics and promotional labels in consumer product

Printing Methods

Printable with letterpress, flexo , offset and gravure.
Please turn off corona unit before printing.

Testing for suitability between media , printers and inks is always recommended prior to use.

Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 \pm 2 °c and 50 \pm 5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.