



### Face Material

Gloss clear top coated polypropylene		
Type	BOPP film	
Colour and Finish	Transparent	
Weight	52 gsm $\pm$ 10%	ISO 536
Thickness	55 $\mu$ $\pm$ 10%	ISO 534

### Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type	Acrylic based	
Min. Appl.Temp	0°c	
Service TEMP	-20/+80 °c	
Initial Tack	9 N/25mm	FINAT FTM 9
Shear	High	FINAT FTM18
Final Adhesion	7 N/25mm	FINAT FTM 2

### Liner

Type	One side siliconized polyester	
Colour and Finish	Transparent	
Weight	32 gsm $\pm$ 5%	ISO 536
Thickness	23 $\mu$ $\pm$ 5%	ISO 534
Transparency	>96%	DIN 53 147-46

### Application

Specially designed for logistics and promotional labels in consumer product

### Printing Methods

Printable with letterpress, flexo , offset and gravure.  
Please turn off corona unit before printing.

Testing for suitability between media , printers and inks is always recommended prior to use.

### Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2 °c and 50 $\pm$ 5 % of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.