



### Face Material

Gloss clear BP film

Type BP film

Colour and Finish Transparent

Weight 50 gsm  $\pm$  10% ISO 536

Thickness 36  $\mu$   $\pm$  10% ISO 534

### Adhesive

General purpose Acrylic permanent featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP)

Type Acrylic based

Min. Appl.Temp 0 $^{\circ}$ c

Service TEMP -20/+80  $^{\circ}$ c

Initial Tack 9 N/25mm FINAT FTM 9

Shear High FINAT FTM18

Final Adhesion 7 N/25mm FINAT FTM 2

### Liner

Type One side siliconized polyester

Colour and Finish Transparent

Weight 50 gsm  $\pm$  5% ISO 536

Thickness 36  $\mu$   $\pm$  5% ISO 534

Transparency >96% DIN 53 147-46

### Application

Specially designed for logistics and promotional labels in consumer product

### Printing Methods

Printable with letterpress, flexo , offset and gravure.

Testing for suitability between media , printers and inks is always recommended prior to use.

### Shelf life

Two years under storage conditions (This material must be stored at a temperature of 23 $\pm$ 2  $^{\circ}$ c and 50 $\pm$ 5  $^{\circ}$ c of relative Humidity.)

Keep the material in the original packaging when not used in order to protect it from dust and contamination

Do not expose to direct sunlight or heat sources.